



WCB

Compac Cabinet 6-9-15 RMS

Part No	Capacity/U	Width/mm	Depth/mm	Height/mm
WCB06-645	6U	600	450	368
WCB09-645	9U	600	450	501
WCB15-645	15U	600	450	769

Especificaciones:

Standard:

Comply with ANSI/EIA RS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92 standard.
Compatible with metric, ETSI and 19' international standard.

Features:

- Exquisite design with precise dimension and craftsmanship.
- International popular smoky-gray glass front door.
- Easily be mounted on wall, or placed on floor after installed castor or feet.
- Loading capacity: 60KG.
- Top and bottom wiring channel could be closed.
- Removable front door and side panel, easily installing and maintaining
- Surface finish: Degreased, acid cleaned, phosphoric, water cleaned, electro-static powder coating, meet ROHS standard.
- Optional color: black/gray
- Optional accessories.

Applications:

Widely used in network system, educational system, broadcasting system and telecommunication system. Suitable for placing server computer and precision electronic equipments.

Materials:

- **WCB**
Cool rolled steel
Thickness: Vertical rail:1.5mm
Else in 1.2mm
Tempered smoky-gray glass with thickness of 5mm.
- **WCE**
Cool rolled steel
Thickness: mounting rail:1.2mm
Else in 0.8mm
Tempered smoky-gray glass with thickness of 5mm.

